

POS 4600 Series

axon
p o s

The POS 4600 Series is ideal for easy service and upgrade at an affordable price. A choice of 12.1", 15", 17" Touch Screens with tilt angle from 0° ~ 60° degree offers you maximum flexibility and convenience. All I / O connectors are covered under the rear cover to provide easier maintenance and better cable management.

- **Cost effectiveness**


- All-in-one MB design for saving material cost of IO card & cable
- System mechanism leveraged over other products

- **Service effectiveness**

- Compact interconnections at mechanical design to save screws and service time
- Hatch-back base cover for efficiency of disassembly



Features



1. Tilt Angle 0° ~ 60° degree



4. Easy to maintain and service
Less than 4 screws to reach key components



2. MSR / Finger print
MSR / I-Button



5. Customer display pole type
VFD type (2 x 20)
LCD type (graphic)



3. Thumb screw design
easy to open rear cover



6. Front I / O cover

axon

POS 4600 Series

A full range of P4-based touch POS terminals providing on-site service with tool-free process

Specification

Model Name	AXP1045/41053	AXP1050/1057	
Motherboard	B81		
CPU Supports	mP478-Pin CPU socket FSB400Mhz, Celeron M 1.2G, Celeron 2.0G / 2.5G, P4 2.0G		
Chipset	852GM +ICH4		
System Memory	2 x 184-pin DIMM socket DDR 200 / 266 up to 2GB		
Graphic Memory	Share System Memory		
LCD / Touch Panel			
LCD Size	12.1" TFT	15" TFT	17" TFT
Brightness (cd / m ²)	150 - 400 cd / m ²	250 -350 cd / m ²	300 cd / m ²
Maximal Resolution	800 x 600 / 1024 x 768	1024 x 768	1280 x 1024
Touch Screen Type	Resistive		
Tilt Angle (Degree)	0° ~ 60°		
Storage			
HDD	1 x 3.5" HDD drive bay		
Flash Memory	Compact Flash (Type I & II)		
Expansion			
Mini-PCI Socket	1		
External I / O Ports			
Front I / O			
USB	2 (V1.1 / 2.0)		
Rear I / O			
PS2	2 (1 x PS2 keyboard, 1 x PS2 mouse)		
USB	2 (V1.1 / 2.0)		
Serial / COM	4 (Pin 1 / 9 with 5V / 12V)		
Parallel	1		
LAN (10 / 100)	1		
2nd VGA	1 x female type connector with power		
Cash Drawer Port	2 (12V / 24V)		
Internal Interface			
USB	USB 5, 6		
COM	COM5 for touch, COM6 for MSR		
Control / Indicator			
Power Button	1		
Indicator LED	1		
Power			
Power Supply	250W ATX		
Environment			
EMC & Safety	FCC / CE Class A, LVD		
Operating Temperature	5°C ~ +35°C		
Storage Temperature	-20°C ~ 60°C		
Operating Humidity	20% - 80% RH non condensing		
Storage Humidity	20% - 85% RH non condensing		
Peripheral			
3-in-1 MSR module	MSR (PS2 / RS-232) / Smart IC card (USB) / I-button (PS2 / RS-232)		
2-in-1 MSR module	MSR (PS2 / RS-232) / Finger Print (USB)		
Output Device			
Second Display	8.4" / 10.4" / 12.1" TFT		
Customer Display	Pole Display / flush mount VFD / LCD customer display		
Communication			
Wireless LAN	Mini PCI 802.11 a / b / g WI-FI card and antenna		
Dimension (W x D x H)	323 x 355 x 182 mm / 13.7" x 15" x 7.7"	378 x 365 x 182 mm / 16" x 15.4" x 7.7"	410 x 373.7 x 192.8 mm / 17.4" x 15.9" x 8.2"
Weight	N.W. 8KGS / G.W. 9KGS	N.W. 9KGS / G.W. 10KGS	N.W. 10KGS / G.W. 11KGS
OS Support	Vista, Windows XP, WEPOS, XP Embedded, XP professional for Embedded, WIN 2000 professional Embedded, Linux		

Product specification subject to change without prior notice.



AXON Computer

Via Taliercio, 7/A
30030 - Gardigiano di Scorzè (VE)
Italy
Tel: +39.041.5830594
Fax: +39.041.5830595
E-mail: info@axoncomputer.it
www.axoncomputer.it

Direzione Commerciale

Via Napoli, 125 - c/o Centro Commerciale Meridiana - 80013 Casalnuovo (NA) - Tel. +39.081.3176051 - Fax +39.081.3176051

Filiale Commerciale

Via Verdi, 6 - 20025 Legnano (MI)